

PRODUCT DATA SHEET:

Mineral Thickeners



Life Sciences

Bentonite 4446 BC - White

Bentonite 4446 is used extensively in pharmaceutical products, personal care products and cosmetics. This grade of bentonite is typically water-washed to remove impurities and lower the grit content.

Cosmetics - High purity bentonites are used in cosmetic preparations as pigment binders and suspending agents. They are also used as thickeners in lotions, creams, liquid facial cleansers, anti dandruff shampoos, body powders, deodorant sprays, deodorant sticks, etc.

TYPICAL PHYSICAL PROPERTIES	
Dry Brightness	83 - 87
Specific Gravity	2.50
Swelling Power (ml)	24+
Gel Formation (max ml)	2.0
% Thru 200 Mesh	100

BSI Code: 4446

INCI: Bentonite

C.A.S. Number: 1302-78-9

Name: Albagel

TYPICAL CHEMICAL PROPERTIES	
SiO ₂ - Silicon Dioxide (%)	59.0 - 61.0
Al ₂ O ₃ - Aluminum Oxide (%)	20.0 - 22.0
Na ₂ O - Sodium Oxide (%)	3.5 - 4.0
MgO - Magnesium Oxide (%)	3.5 - 4.0
CaO - Calcium Oxide (%)	2.0 - 3.0
Fe ₂ O ₃ - Ferric Oxide (%)	0.6 - 0.7
K ₂ O - Potassium Oxide (%)	0.02 - 0.03
TiO ₂ - Titanium Dioxide (%)	0.10 - 0.20
Moisture (%)	8.0
pH Value	9.5 - 10.5

Storage: Store in cool location, keep away from heat and direct sunlight. Keep container sealed.

Handling Precautions: Please refer to the Bentonite 4446 BC Safety Data Sheet.

While the data presented in this information sheet reflects the present state of our knowledge and is believed to be accurate and reliable, it is provided without liability as a courtesy only and is to be used and relied upon at the reader's sole risk. Readers should make their own determination as to the suitability of any product for a particular use. We recommend that readers conduct their own product trials before using any particular product. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties rights. The recommendations contained herein do not constitute a warranty, either express or implied, as to the fitness or suitability of any product for a particular purpose. For more information and assistance, please contact Technical Services at BSL_regulatory_dept@brenntag.com

Brenntag Specialties, LLC / 1 Cragwood Rd, Suite 302, South Plainfield, NJ 07080 / 800.732.0562