

Specifications for
LILAC® G

(INCI name: C15-23 Alkane and C13-14 Alkane)

<u>PROPERTIES GUARANTEED</u>	<u>TEST METHOD</u>	<u>LIMITS</u>
Specific Gravity @ 25°C/25°C	ASTM D4052	0.810/0.830
Kin. Viscosity @ 40°C, mm ² /s	ASTM D445	3.9/5.0
Acidity	ASTM D974	<0.05
Readily Carbonizable Substances	ASTM D565	<16Helige Amber C
Limit Of Polynuclear Compounds	ASTM D2269	<0.100 Abs.
Odor	LATM 092	NONE
Color, Saybolt	ASTM D156	30 Min.

TYPICAL PROPERTIES FOR LILAC® G

<u>PROPERTIES</u>	<u>TEST METHOD</u>	<u>TYPICAL VALUE</u>
Flash Point, COC, °C	ASTM D92	140 (120 Min)

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.