

WESTON[®] 619F phosphite

Phosphite Antioxidant


Description

WESTON[®] 619F phosphite is a phosphite that is a highly effective color and molecular weight stabilizer for polyolefins, polyesters, elastomers, styrenics, engineering thermoplastics, and adhesive formulations. It also contributes to the thermal and UV stability of these polymers. This product is available in a flake form.

Chemical Structure

Distearyl Pentaerythritol Diphosphite $C_{41}H_{82}O_6P_2$

Chemical Abstract Number: 3806-34-6



⁽¹⁾ **WESTON[®] 619F phosphite** contains no more than 1% by weight of Triisopropanolamine (CAS# 122-20-3).

Typical physical properties of WESTON[®] 619F phosphite

Appearance	White Flakes
Specific Gravity @ 60°C/15.5°C	0.920-0.935
Acid No. (mg KOH/g)	1.0 max
Refractive Index @ 60°C (140°F)	1.4560 - 1.4590
Phosphorus Content (%)	7.8-8.2
Flash Point (Pensky-Martens Closed Cup)	188°C (370°F)
Bulk Density [lb./ft ³] & [g/ml]	27 & 0.43
Melt Range	37-46°C (99-115°F)
Formula Weight	732

Solubility @ 25°C (77°F)g/100g

Acetone	0.3	Cyclohexane	20.0
Benzene	14.7	Hexane	25.0
Chloroform	45.0	Toluene	30.0
Corn oil	0.4	Water	<0.1

Note: Solutions may be cloudy.

Soluble in most common aprotic organic solvents

The information contained herein relates to a specific AddivantTM product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet shall be construed to modify any of AddivantTM standard terms and conditions of sale under which the product is sold by AddivantTM. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSTRUED TO CONSTITUTE A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ANY AND ALL SUCH REPRESENTATIONS AND WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner.

AddivantTM and the AddivantTM logo are trademarks of AddivantTM Corporation or one of its subsidiaries.

Copyright © 2013 AddivantTM Corporation. All rights reserved.

Product Features

- Excellent color stability during processing, fabrication and end use
- Polymer protection from degradation during processing
- Reduced discoloration of polymers containing pigments such as TiO₂
- Reduced discoloration of polymers that are stabilized with a sulfur-containing, nickel-organic complex and are processed at high temperatures
- Synergism when used with light stabilizers such as benzophenones and benzotriazoles
- High performance at low loading levels for more cost effective formulations


Food Contact Regulatory Status

WESTON[®] 619F phosphite complies with 21 CFR 178.2010 for use in many polymers. Also listed with Germany (BfR) and other EU member state regulations. Consult the regulations for limitations and restrictions before use.

For details please contact Addivant[™] Regulatory Affairs Polymer Additives.

Volatility by Thermal Gravimetric Analysis

Conditions: Nitrogen atmosphere @ 20°C (36°F)/minute.



The information contained herein relates to a specific Addivant[™] product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet shall be construed to modify any of Addivant[™] standard terms and conditions of sale under which the product is sold by Addivant[™]. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSTRUED TO CONSTITUTE A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ANY AND ALL SUCH REPRESENTATIONS AND WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner.


Addivant[™] and the Addivant[™] logo are trademarks of Addivant[™] Corporation or one of its subsidiaries.

Copyright © 2013 Addivant[™] Corporation. All rights reserved.

Viscosity vs. Temperature

WESTON® 619F phosphites tested in air.

Heating rate 5°C/minute



Storage and Handling

The product may be stored at least one (1) year in sealed containers. Containers should be stored in a cool, dry area. Extended storage at elevated temperatures or exposure to direct heat could decrease product shelf life. Containers should be kept sealed when not in use.

Open containers should be used as soon as possible (maximum 4 months) to avoid hydrolysis, especially during humid weather.

For additional handling and toxicological information consult the Addivant[™] Material Safety Data Sheet.

The information contained herein relates to a specific Addivant[™] product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet shall be construed to modify any of Addivant[™] standard terms and conditions of sale under which the product is sold by Addivant[™]. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSTRUED TO CONSTITUTE A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ANY AND ALL SUCH REPRESENTATIONS AND WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner.

Addivant[™] and the Addivant[™] logo are trademarks of Addivant[™] Corporation or one of its subsidiaries.

Copyright © 2013 Addivant[™] Corporation. All rights reserved.