

INTRODUCTION

Ucecryl B 1009 is a high MFFT straight acrylic emulsion copolymer.

SUGGESTED APPLICATIONS

Hydrophobic paints for fibre-cement sheets.

PERFORMANCE HIGHLIGHTS

Ucecryl B 1009 is :

- ✓ Xi-free

UCECRYL B 1009 Product data

Determined per batch :

Appearance (D0201100)	: milky liquid
Solids content(2h at 105°C) (D0001000)	: 47.0 – 49.0 %
Brookfield viscosity (At 25 °C-50 rpm) (D0059500)	: 200 - 800 mPa.s
pH measurement (D0002000)	: 7.5 – 9.5

Not continually determined :

MFFT (D0150000)	: + 41 °C
--------------------	-----------

RECOMMENDED FORMULATIONS

Contact us.

STANDARD PACKAGING

Ucecryl B 1009 is available in the following standard packaging:

- Bulk
- 1000 kg one way white PE schütz container, 3 inch

Any other special packaging should be requested to the sales account representative.

PRECAUTIONS

Appropriate precautions should be taken to avoid eye and skin contact .

Please refer to the Material Safety Data Sheet for further details.

STATUTORY LABELLING

This product **has not to be labeled** according to European Directive 67/548/EEC, 1999/45/EC and its adaptations and amendments.

See Material Safety Data Sheet for emergency and personal protection guides.

TRANSPORT REGULATIONS

Not subject to special regulations.

See Material Safety Data Sheet for more information.

STORAGE AND HANDLING

See Material Safety Data Sheet for more information.