

## INTRODUCTION

Ucecryl B 3022 is a medium MFFT straight acrylic emulsion copolymer. Coatings based on Ucecryl B 3022 exhibit a good adhesion to various substrates. They are characterized by a good resistance to water whitening and a good weathering resistance.

## SUGGESTED APPLICATIONS

Clear coats for wood.

## PERFORMANCE HIGHLIGHTS

Ucecryl B 3022 is :

- ✓ Free of alkylphenol ethoxylates (APEO)
- ✓ Xi-free

## UCECRYL B 3022 Product data

### Determined per batch :

Appearance (D0201100)	: milky liquid
Solids content(2h at 105°C) (D0001000)	: 43.5 – 45.5 %
Brookfield viscosity (At 25 °C-50 rpm) (D0059500)	: 50 - 1250 mPa.s
pH measurement (D0002000)	: 8.0 – 9.5

### Not continually determined :

MFFT (D0150000)	: 12°C
--------------------	--------

## RECOMMENDED FORMULATIONS

Contact us.

## STANDARD PACKAGING

Ucecryl B 3022 is available in the following standard packaging:

- Bulk
- 1000 kg one way white PE schütz container, 3 inch

Any other special packaging should be requested to the sales account representative.

## PRECAUTIONS

Appropriate precautions should be taken to avoid eye and skin contact . Please refer to the Material Safety Data Sheet for further details.

## STATUTORY LABELLING

This product **has not to be labeled** according to European Directive 67/548/EEC, 1999/45/EC and its adaptations and amendments. See Material Safety Data Sheet for emergency and personal protection guides.

## TRANSPORT REGULATIONS

Not subject to special regulations. See Material Safety Data Sheet for more information.

## STORAGE AND HANDLING

See Material Safety Data Sheet for more information.