

Product Data

NUMBER 4409-1

Strodex[®] PK-0VOC Phosphate Ester Surfactant For Waterborne Architectural Coatings

Strodex[®] PK-0VOC surfactant is the neutralized (potassium salt) form of a phosphate coester of aliphatic alcohols. It is designed to impart improved gloss and color acceptance in waterborne latex paints. Depending on the formulation specifics, Strodex[®] PK-0VOC surfactant can also function as a supplemental dispersant to assist in reduction of pigment flocculation. Strodex[®] PK-0VOC surfactant does not contain any alkyl phenol ethoxylates (APEOs).

Strodex[®] PK-0VOC surfactant is particularly beneficial at wetting pigments including TiO₂, iron oxides and common extenders. Spreading and uniform coverage of paint on difficult to wet surfaces are improved by the use of Strodex[®] PK-0VOC surfactant.

Typical Properties^(a)

Chemical type	Phosphate Ester (anionic)
Appearance.....	Clear liquid
Active solids, weight %.....	42 ± 2%
Gardner Color	2 maximum
Viscosity ^(b) , as supplied (cps or mPa-s).....	230 – 330
Density, g/mL	1.10
Density, lb/gal.....	9.2
pH, 10% aqueous solution	8.5 – 9.5
Flash point ^(c)	> 200°F (93°C)

^(a) Values are typical properties and are not to be regarded as product specifications.

^(b) Brookfield RVT viscosity at 25°C (77°F), spindle #5 at 30 rpm.

^(c) Tag closed cup

(continued)

Hercules Incorporated and its Aqualon subsidiary (together referred to as "Hercules") believes that all information provided with respect to its products is accurate at the time such information is provided. Unless otherwise agreed, Hercules makes no express, implied, or other representation, warranty, or guarantee concerning such information or the handling, use, or application of its products, whether alone or in combination with other products, except that its products are of Hercules' standard quality. Users of Hercules' products are advised to perform their own tests to determine the safety and suitability of each such product or product combination. Users are urged to read and understand the Material Safety Data Sheet (MSDS) and to abide by all use and safety recommendations detailed therein and on all product labeling. Hercules does not recommend the use of its products in any manner which would violate any patent or intellectual property rights. Unless otherwise agreed, the purchasers of Hercules' products assume all responsibility and liability for all loss or damage arising from the improper handling or use of our products. This disclaimer supersedes any prior or different disclaimers for this product.



Product Benefits

- Increases gloss
- Reduces hazing
- Enhances color properties
- Improved substrate wetting
- Excellent wetting & dispersion of pigments including iron oxides
- Improved freeze-thaw resistance
- Helps prevent crawling, cratering & pinholing
- Low water sensitivity
- Inhibition of flash & nail head rusting
- May improve open time & block resistance

Recommended Use Levels

- In flat, semi-gloss and gloss paints, 8-14 pounds of Strodex[®] PK-0VOC surfactant per 100 gallons of finished paint are recommended.

Volatile Organic Compounds (VOCs)

Strodex[®] PK-0VOC surfactant is formulated as solvent-free. As such, the VOC content of this product should be non-detectable using the standard U.S. EPA Reference Method 24.

APEO & Glycol Content

Strodex[®] PK-0VOC surfactant does not contain any alkyl phenol ethoxylates (APEOs). Glycols are not intentionally added or known to be present in Strodex[®] PK-0VOC surfactant.

Chemical Inventories

All components of Strodex[®] PK-0VOC surfactant are listed on TSCA chemical inventory (USA).

Product Safety

Please read & understand the MSDS before using this product.

Dextrol[®] and Strodex[®] are registered trademarks of Hercules Incorporated

08-08

© Hercules Incorporated, 2008