

TECHNICAL DATA SHEET:

Stearates - Technical Grade



Material Sciences

Stearates - Technical Grade - 2310-G - Zinc GP Veg

2310-G is a xtra fine particle size grade of zinc stearate. Zinc stearate can perform the following functions in formulations; lubricant, acid scavenger, coupling agent, waterproofing agent, viscosity modifier and flattening agent. Zinc stearates are used in the production of color concentrates, fiberglass reinforced polyesters, phenolic resins and compounds, polyolefins, polystyrene, PVC, coatings, varnishes, sanding sealers, rubber articles and compositions and in metal forming operations such as, stamping, extrusion or milling.

BSI Code: 2310-G

Description: Lacquer-XF

Grade: Tallow

C.A.S. Number: 557-05-1

Storage Life: 24 months from date of manufacture in the original sealed container at ambient temperature. Store away from excessive heat and humidity.

Handling Precautions: Please refer to the Zinc Stearate Safety Data Sheet.

TYPICAL PROPERTIES

Ash (%)	13.2 - 14.2
Moisture (max %)	1.0
Bulk Density (g/cc)	0.20 - 0.25
Melting Point (°C)	118 - 122
% Thru 400 Mesh	99.0
pH Value	6.0 - 7.0

CFR REFERENCES:

2310-G Zinc Stearate is suitable for use in food packaging applications in accordance with the following FDA Code of Federal Regulations:

21CFR175.105 - Adhesives.

21CFR175.300 - Resinous and polymeric coatings (xxii).

21CFR176.170 - Components of paper and paperboard in contact with aqueous and fatty foods.

21CFR176.180 - Components of paper and paperboard in contact with dry food.

21CFR177.1900 - For use as a lubricant in urea-formaldehyde resins in molded articles.

21CFR177.2410 - For use as a lubricant in phenolic resins in molded articles.

21CFR177.2600 - For use as an activator in rubber articles intended for repeated use.

21CFR178.2010 - Antioxidants and/or stabilizers for polymers.

21CFR182.8994 - Zinc Stearate.

While the data presented in this information sheet reflects the present state of our knowledge and is believed to be accurate and reliable, it is provided without liability as a courtesy only and is to be used and relied upon at the reader's sole risk. Readers should make their own determination as to the suitability of any product for a particular use. We recommend that readers conduct their own product trials before using any particular product. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties rights. The recommendations contained herein do not constitute a warranty, either express or implied, as to the fitness or suitability of any product for a particular purpose. For more information and assistance, please contact Technical Services at BSL_regulatory_dept@brenntag.com

Brenntag Specialties, LLC / 1 Cragwood Rd, Suite 302, South Plainfield, NJ 07080 / 800.732.0562