

# BKS 2600 Resin

866-4GP-CHEM  
www.gp-chemicals.com  
Fax: 770-322-9973

## Product Information

### DESCRIPTION

BKS 2600 phenolic resin for protective coatings for rigid metallic substrates is formulated to provide chemical resistance for applications such as drums and pails, pipes, tanks and rail-cars.

It is a heat-reactive phenolic resin solution in ethanol.

### CERTIFICATIONS

Conforms to 21 CFR for: 175.105, 175.300, 176.170, 176.180, 177.1210

### STORAGE AND HANDLING

BKS 2600 resins are packaged in drums and are heat-reactive resins with a limited shelf life. Extended storage at high temperatures should be avoided to prolong the useful life of the resins. It is suggested that the resin be stored at or below 60°F in order to maximize storage life. BKS resins should be used in a well-ventilated area.

### TYPICAL PROPERTIES

Form	Solution in ethanol
Viscosity @25°C, cP (mPa*sec)	700 – 1000
Solids, wt. %	52 – 56
Specific Gravity @25°C	1.04 – 1.07



bonds that last. advancements that work.™

The Georgia-Pacific logo and bonds that last. advancements that work are trademarks owned by or licensed to Georgia-Pacific Chemicals LLC. © 2012 Georgia-Pacific Chemicals LLC. All rights reserved. IND-0058-1207

The technical data/information herein is believed to be accurate. It is offered for your consideration, investigation, and verification. Buyer assumes all risk of use, storage, and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE WHICH ARE SPECIFICALLY EXCLUDED. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.