

# Products & Technologies

## CK-2500 Resin

Modifier for alkyd and epoxy air dry coatings designed to improve water resistance, hardness, gloss and intercoat adhesion.

### Applications

Coatings, Inks, Protective coatings: Marine and maintenance, Protective coatings: Metal protection, Varnishes

### Product Composition

Novolac resin

### Appearance/Form

Solid, flake

### Certifications

Conforms to 21 CFR for: 175.105, 175.300, 176.170, 176.180, 177.1211

### Typical Properties

<b>Softening Point, °F (°C)</b>
220 - 240 (104 – 116)
<b>Color, Gardner (50:50 in Xylene)</b>
8 maximum

### Packaging

Bags

### Storage and Handling

CK-2500 novolac resins are non heat-reactive and should be stored in a dry location at temperatures below 35°C. Storage in sunlight should be avoided. Resin storage life under the recommended conditions is two years, possibly longer - but it may need to be recertified after two years. The resins should be stored in a well ventilated area.

The information and technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WHICH ARE SPECIFICALLY EXCLUDED. Nothing contained herein shall be construed as a license to operate under or recommendation to infringe any patents.