



TECHNICAL DATA SHEET

Setal 10-1010

Polyethylene wax dispersion
(Brazil product number: RALWAX 1010)

General description:

Setal 10-1010 is polyethylene wax dispersion that is used to improve aluminum orientation and anti-sedimentation.

Technical features:

1. Aluminum orientation
2. Anti-sedimentation

Suggested uses:

1. Automotive and industrial paint systems
2. Metallic base coats

Delivery form: 6.3% non-volatile in butyl acetate/ xylene/ n-butyl acetate (58/ 32/ 10 pbw)

Typical Properties:

Property	Value	Units	Method *
Non-volatiles, by weight	6.3 ± 1.0	%	1 – 1
Grit	Pass	Visual	15 – 1
Appearance	Milky	Visual	7 - 1

* SDM: Nuplex Resins methods of determination (available on request)

Density: 7.29 ± 0.10 lbs./gal
HEW, on solids: 380
Flash point: 46 °F Setafash
Reduced Viscosity D – F @ 60% N/V in MPK
Non-volatiles, by vol 2.2%

On DSL Inventory

Updated: May, 2014

All information, recommendations and suggestions, concerning the product and its use, are believed to be reliable. However, Nuplex Resins gives no assurance as to the accuracy, completeness, or adequacy for a particular purpose. It is the user's responsibility to determine the suitability for its own use of the products. No guarantee (whether expressed or implied) is made by Nuplex Resins as to the results to be obtained from using the described products, nor shall Nuplex Resins be liable for any use by others of the described products. Users are responsible for ensuring compliance with local legislation and obtaining the necessary certifications and authorizations. All orders are subject to the general conditions of sale of Nuplex Resins, which are printed overleaf and/or can be downloaded from www.nuplexresins.com. All of user's general terms and conditions are herewith deemed rejected. Nuplex Resins owns all copyrights and other intellectual property rights in the contents of this document. Reproduction or redistribution in any form is not allowed.