



TECHNICAL DATA SHEET

SETAQUA 6498

An acrylic terpolymer emulsion (37-6498)

General description:

SETAQUA 6498 is a high performance, hard acrylic terpolymer for a range of applications including concrete and roof tile coatings.

Technical features:

1. Exceptional exterior durability and hardness
2. Excellent adhesion and water resistance
3. Passes water retention requirement of ASTM C1315

Suggested uses:

1. Concrete and Roof Tile Coatings
2. Clear Glazes and Coatings where hardness and durability are required
3. Concrete curing membrane

Delivery form: 45% n.v. in water

Typical properties:

Property	Typical Value	Units	Method *
Non-volatile, by wt.	45.0	%	1 – 1
Viscosity, Brookfield	100	cps	2 – 2
pH	7.7		8 – 1

* SDM: Nuplex Resins methods of determination (available on request).

MFFT: 30 °C
Particle Size: 0.10 microns
Density: 8.65

On the DSL Inventory

Updated: October, 2013

All information, recommendations and suggestions, concerning the product and its use, are believed to be reliable. However, Nuplex Resins gives no assurance as to the accuracy, completeness, or adequacy for a particular purpose. It is the user's responsibility to determine the suitability for its own use of the products. No guarantee (whether expressed or implied) is made by Nuplex Resins as to the results to be obtained from using the described products, nor shall Nuplex Resins be liable for any use by others of the described products. Users are responsible for ensuring compliance with local legislation and obtaining the necessary certifications and authorizations. All orders are subject to the general conditions of sale of Nuplex Resins, which are printed overleaf and/or can be downloaded from www.nuplexresins.com. All of user's general terms and conditions are herewith deemed rejected. Nuplex Resins owns all copyrights and other intellectual property rights in the contents of this document. Reproduction or redistribution in any form is not allowed.