



# Sales Promotion

## Poraver<sup>®</sup> 0.25-0.5 mm



### Recommended Application Usage

- Veneerstone mix designs
- Precast concrete - ornamental/decorative glass fiber reinforced concrete/countertops
- Self levelling underlayments
- Mortars - medium bed cementitious tile adhesive/concrete repair mortar
- Moulding & plaster
- Shotcrete, grouts and marine screed

### Promotion Details

- Poraver<sup>®</sup> grain size 0.25-0.5 mm
- High stock
- Readily available
- 50 cubic feet supersacks
- 1,047 lbs each
- Special price, limited time only

Please contact your sales representative for inquiries and additional information:



**Traves W. Ogilvie**  
Sales Manager  
Eastern USA  
Phone: +1 401 636 0455  
Fax: +1 705 431 2701  
Email: togilvie@poraver.com

PROPERTIES		STANDARD	PORAVER <sup>®</sup>
Grain size	[mm]	ASTM C136	0.25-0.5
Fineness modulus			1.92
Dry loose bulk density	[kg/m <sup>3</sup> ]	ASTM C9/C29M	340 ± 30
Compressive strength	[MPa]	EN 13055-1	≥ 2.60
Overgrain			≤ 10% by mass
Undergrain			≤ 15% by mass
Organic impurities		ASTM C40	no injurious compounds

The following data are valid for all grain sizes:

pH value		8-12
Moisture content on delivery		≤ 0.5 %
Softening point		approx. 700 °C / 1,300 °F
Color		creamy white
	[Y]	> 48
Thermal conductivity	[W/m·K]	0.082