



NEW! **PORAVER**[®]
SPECIAL BLEND
0.25-1 mm

ALL PURCHASE ORDERS FOR SUPERSACKS OF OUR SPECIAL BLEND WILL BE INVOICED AT THE INTRODUCTONAL PRICE. VALID UNTIL DECEMBER 2018

PROPERTIES SPECIAL BLEND	STANDARD	PORAVER [®]
Grain size [mm]	ASTM C136	0.25-1
Fineness modulus		2.24
Dry loose bulk density [lb/ft ³]	ASTM C9/C29M	19.4 ± 1.9
Compressive strength [psi]	EN 13055-1	≥ 333.6
Overgrain		≤ 10% by mass
Undergrain		≤ 15% by mass
Organic impurities	ASTM C40	no injurious compounds
The following data are valid for all grain sizes:		
pH value		8-12
Moisture content on delivery		≤ 0.5 %
Softening point		approx. 700 °C / 1300 °F
Color		creamy white
	[Y]	> 48
Thermal conductivity	[W/m·K]	0.082
	[BTU-in/h·ft ² ·°F]	0.569

Promotion Details

- Poraver grain sizes 0.25-0.5 mm & 0.5-1 mm
- New special blend ratio 50:50
- 50 cubic feet supersacks
- 950 lbs each
- Special price: \$0.30/lb

USD \$285 each supersack

Recommended Application Usage

- Veneerstone mix designs
- Precast concrete
- Mineral casting
- Polymer concrete
- Stucco & plaster



For additional information please contact:
Traves W. Ogilvie
Sales Manager
Eastern USA
Phone: +1 401 636 0455
Fax: +1 705 431 2701
Email: togilvie@poraver.com