



Southeastern Performance Minerals, LLC NHA 60 Muscovite Mica

General Description

NHA 60 is a proprietary blend of muscovite mica produced to impart structural strength, flexural and tensile, in variety of coating and functional filling applications. Additionally, the wide particle size distribution gives NHA 60 a wide variety of applications where coverage, surface area, and sound dampening are crucial.

Stucco	Sound Deadening
Asphalt Coatings	
Plastics	
Paints & Coatings	

Typical Properties

Sieve Analysis	% retained
+20 mesh	<5.0%
+100	>50%
+325	>80%
Bulk Density (Colgate)	<40
Moisture Loss @ 100°C	<0.5%
Specific Gravity	2.65-2.82
pH	6.0-7.5
CAS No.	12001-26-2

See SDS for safety and regulatory information.

Southeastern Performance Minerals, LLC
1132 Veal Rd.
Sandersville, GA 31082

Phone: (478)553-0048
Fax: (478)553-0050
info@sepm.us

The statements herein are based on data which is believed to be reliable. This data is offered in good faith and typical of normal production. SEPM make no warranty or representation, expressed or implied, regarding the accuracy of this data or the use of this product. The user is solely responsible for the use of this product.

Issue date: 5/1/17

Revised date: 6/18/18