



Southeastern Performance Minerals, LLC

PMica 55 Muscovite Mica


General Description

PMica 55 is a wet ground muscovite mica, processed specifically for industrial applications. Proprietary milling and processing induces a high degree of delamination and narrow particle size distribution, which translates to high aspect ration and increased resiliency. These characteristics make PMica 55 an acceptable, cost effective additive for the following markets:

- | | |
|------------------|-------------------|
| Roof Coatings | Plastics |
| Mold Releases | Paints & Coatings |
| Foundry Coatings | Cultured Stone |
| Gaskets | |

Typical Properties

Sieve Analysis	% retained
+100 mesh	trace
+325 mesh	30-40
Bulk Density (Colgate)	10-14
Mean Particle Size (µm)	48-55
Color, L* value	>88
Moisture Loss @ 100°C	<0.5%
Specific Gravity	2.82
pH	6.0-7.5
CAS No.	12001-26-2



See SDS for safety and regulatory information.

Southeastern Performance Minerals, LLC
 1132 Veal Rd.
 Sandersville, GA 31082

Phone: (478)553-0048
 Fax: (478)553-0050
info@sepm.us

The statements herein are based on data which is believed to be reliable. This data is offered in good faith and typical of normal production. SEPM make no warranty or representation, expressed or implied, regarding the accuracy of this data or the use of this product. The user is solely responsible for the use of this product.

Issue date: 6/11/15

Revised date: 7/23/18