



CTC-PDS-NA-ReNew SC4003-R2

## ReNew™ SC4003 contaminant control

### Product Description

ReNew™ SC4003 contaminant control is a multi component non caustic spray-on cleaner that is ideal for machine frames floors and general cleaning.

A light foam is produced when applied that is easily removed with rinsing.

Use ReNew SC4003 to economically remove floor grime, hardened stock, and general machine deposition.

### Product Application

ReNew SC4003 is applied through a foaming unit at a 25% to 100% solution.

Using warm water (140 °F) is recommended for product dilution. Once foam is applied, wait 15 minutes and rinse thoroughly with warm water.

ReNew SC4003 is to be used in accordance with control procedures Solenis establishes for a specific application.

### Benefits

- Low cost
- Ideal for machine dryer hoods
- Light foaming tendency is easy to rinse
- Can be used where caustic products are a concern
- Dispersant and surfactant blend is effective at penetrating and dispersing solubilized contaminants

### Packaging

This product is available in a variety of packaging sizes. Your Solenis representative will recommend the appropriate packaging for the application.

### Important Information

**Typical Properties:** Refer to the Safety Data Sheet (SDS).

**Regulatory Information:** Refer to the SDS or contact your sales representative for any additional regulatory and environmental information.

**Safety:** Solenis maintains an SDS for all of its products. Use the health and safety information contained in the SDS to develop appropriate product handling procedures to protect your employees and customers.

Our SDS should be read and understood by all of your supervisory personnel and employees before using Solenis products in your facilities.